

PRODUCT SHEET

| | | | |
|----------------------|---|-----------------------|----------------------------|
| Brand name: | BN Walls | | |
| Serie name: | Lobby | | |
| General description: | HT Non Woven Backed vinyl wallcovering BioPruf® treated | | |
| Measurements: | Width: | 130 cm | 51 inch +/- |
| | Roll Length: | 50 mtr | 54 yard +/- |
| | Weight: | 355 gr/m ² | 15 oz/ly +/- EN ISO 2286-2 |
| | Pattern repeat: | free match | |
| Fire ratings: | Euroclass: | B-s1-d0 | EN 13501-1 |
| | ASTM: | Class A | |
| | IMO: | Available on request | |
| Hanging instruction: | Non reverse/straight | | |
| Light fastness: | ≥ 7 International Woolscale - BS EN 20105 / ISO 105-B02 | | |
| Washability: | Scrubbable (depends on embossing/structure) - EN 259-1 / EN 12956 | | |
| Resistant to: | Most cleaning products, households detergents and chemicals (summary on demand) | | |
| Not resistant to: | Solvents like Ketones; Esters; Aromatic hydrocarbons | | |
| Safety/Ecological: | The material is classified as non-hazardous. For more information see safety datasheet according to DIN 52900 or 91/155/EEG, 2001/58/EC | | |
| Certifications: | FSC® certified - FSC-C100728 | | |
| Other features: | Extra stain resistant toplayer Non solvent based inks and top coatings BioPruf® prevents the growth of mold/mildew and bacteria Good impact resistance (EN 259-2) High tear resistance International Pollution Prevention and Control (IPPC) | | |
| Installation: | Refer to installation recommendations leaflet inside the core of each roll | | |
| Adhesives: | Heavy duty wallcovering adhesive BK 10 (manual) or similar PVA substitute for absorbing surfaces. BK 30 for non-absorbing surfaces (manual) | | |
| | Product sheet last revised: 17-09-2018 | | |

BN Walls
P.O. Box 2
1270 AA Huizen
The Netherlands

Tel: + 31 35 524 84 39
Mail: info@bnwalls.com
Web: bnwalls.com

