

PRODUCT SHEET

Brand name:	BN Walls		
Serie name:	Osaka		
General description:	Non Woven Backed vinyl wallcovering BioPruf® treated		
Measurements:	Width:	130 cm	51 inch +/-
	Roll Length:	35 mtr	38 yard +/-
	Weight:	450 gr/m2	20 oz/ly +/- EN ISO 2286-2
	Pattern repeat:	free match	
Fire ratings:	Euroclass:	B-s2-d0	EN 13501-1
	ASTM:	Class A	
	IMO:	Available on request	
Hanging instruction:	Non reverse/straight		
Light fastness:	≥ 7 International Woolscale - BS EN 20105 / ISO 105-B02		
Washability:	Scrubable (depends on embossing/structure) - EN 259-1 / EN 12956		
Resistant to:	Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids		
Not resistant to:	Solvents like Ketones; Esters; Aromatic hydrocarbons		
Safety/Ecological:	The material is classified as non-hazardous. For more information see safety datasheet according to DIN 52900 or 91/155/EEG, 2001/58/EC		
Certifications:	International Pollution Prevention and Control (IPPC)		
Other features:	Non solvent based inks and top coatings BioPruf® prevents the growth of mold/mildew and bacteria		
Installation:	Refer to installation recommendations leaflet inside the core of each roll		
Adhesives:	Heavy duty wallcovering adhesive BK 10 (manual) or similar PVA substitute for absorbing surfaces. BK 30 for non-absorbing surfaces (manual)		

Product sheet last revised: 08-02-2017

BN Walls
P.O. Box 2
1270 AA Huizen
The Netherlands

Tel: + 31 35 524 84 39
Mail: info@bnwalls.com
Web: bnwalls.com

